LOAD BANK

KPLB-1375

KEYPOWER®
Anytime Anywhere, Power Solutions

KEYPOWER LOAD BANK:

- Frequency: 50/60 Hz;
- Voltage range: AC 110-690V;
- Duty: Continuous;
- Cooling system: Industrial grade axle fans;
- Discharged air direction: horizontal for 100 kw, vertical for larger models;
- Control power phase: Single-phase, two-wire for 500 kw and below; three-phase, four-wire for larger models.

GENERAL SPECIFICATIONS	
Model	KPLB-1375
Capacity	1375KVA/1100kW
Type of load	Resistive & inductive load
Power factor	0.8/1.0
Duty cycle	Continuous
Cooling system	Industrial grade axial fan
Cooling mode	Forced air-cooled
Airflow	Vertical discharge
Phase	Available at both single and three phase
Rated testing voltage	3P3W 110 - 690V
Rated frequency	50Hz / 60Hz
Number of fans	6
Control power input voltage	3P4W 220 - 480V

50/60 HZ FREQUENCY | DRY TYPE | FORCED AIR COOLED | SOUNDPROOF | CERTIFICATION | ISO 9001

Dimension and Weight



DIMENSION		KPLB-1100
Length (L)	mm	3500
Width (W)	mm	2270
Height (H)	mm	2150
Weight	kg	5600

KEYPOWER has the right to modify any feature without prior notice. Weights and dimensions based on standard products. Illustrations may include optional equipment. Technical data described in this catalogue correspond to the available information at the moment of printing. The illustrations and images are indicative and may not coincide in their entirety with the product. Industrial design under patent.

LOAD BANK

KPLB-1375

KEYPOWER®
Anytime Anywhere, Power Solutions

Technical Specifications

PERFORMANCE PARAMETER	
Ambient Temperature	-10°C ~ +55°C
Relative Humidity	⩽98% ventilated environment without explosive or corrosive dust
Altitude	⩽3000m above sea level
Wire Connection	Socket / Terminal
Load Tolerance (each step)	±5%
Load Tolerance (overall)	±3%
Enclosure	Canopy type
Parameter measuring accuracy grade	0.5
Noise level	83 dBA @ 1m
Enclosure protection class	IP 23
Forklift handling	Yes

CONTROL PANEL	
Control mode (Standand)	Local control
Control mode (Optional)	Remote control
Remote control distance	⩽100 m
Load step	0-10kW*1, 10kW*3, 20kW*3, 50kW*2, 100kW*9 / 0-8kvar*1, 8kvar*3, 15kvar*3, 38kvar*2, 75kvar*9 (non-intelligent type)
	0-10kW*1, 10kW*3, 20kW*3, 50kW*6, 100kW*7 / 0-8kvar*1, 8kvar*3, 15kvar*3, 38kvar*6, 75kvar*7 (intelligent type)
Load bank protections	Fan failure alarm / Overload alarm / Overvoltage alarm / Overheating alarm
Multi functions display	voltage, current, load power, reactive power, apparent power, power factor, frequency etc.
One-step load/unload	Yes
Emergency stop	Yes
Phase sequence indicator	Yes

Optional Items for Load Bank:

- Capacitive/Inductive/Resistive load bank with different power factor
- Intelligent control
- Laptop for remote control
- Generator tester
- Multi-voltage
- Water-proof cover for air outlet (200-1400KW)
- Air deflecting duct for containerized load bank
- Space heater
- Cable connector
- Galvanized sheet canopy
- Wheels for < 500KW load bank
- Trailer

RESISTOR FEATURES	304 STAINLESS STEEL RESISTORS
Material	Stainless steel
Cooling mode	Forced air cooling
Temperature resistance	500 ~ 600°C
Load Tolerance	±5%
Warranty	3 years with unlimited hours

INDUCTOR FEATURES	INDUCTIVE TYPE
Insulation level	Class H
Operating temperature	-25 ~ 60°C
Flame retardant rating	UL94 - V0
Surface treatment	Conformal coating
Fastener treatment	Hot-dip galvanized
Overall treatment	Vacuum impregnation varnish

LOAD BANK

KPLB-1375

KEYPOWER®
Anytime Anywhere, Power Solutions

Generator Tester Function

GENERATOR TESTER

TEST REPORT


Test report of generator set's steady performance

FREQUENCY AND VOLTAGE CURVES



HARMONIC CURVE



This generator tester can measure most electric parameters of a single-phase or three-phase AC generator. The standards it complied with are GB/T 2820-1997 and GB 2820-90. The signal frequency can be measured varies from 45 Hz to 65Hz. You can select one wiring mode from four modes – 1Φ2W, 3Φ3W, 3Φ4W and 3V3A. The following table shows the parameters: It's the best way to replicate, prove and verify the real-life demands on critical power systems.

MEASUREMENT MODE	PARAMETERS
Normal	Voltage, Current, Active Power, Reactive Power, Apparent Power, Power Factor, Frequency, Energy runtime, Imbalance degree of Voltage
Harmonic	Voltage & Current: 2~50th order and the THD (Total harmonic distortion)
Adjustment	In 100 seconds: Records the maximum & minimum value of Voltage & Frequency. Calculates the increase & decrease range of Voltage & Frequency and the percentage of adjustment.
Fluctuation	In 60 seconds: Records the maximum & minimum value of Voltage & Frequency. Calculates the NORMAL frequency rang, NORMAL voltage offset, voltage modulation, percentage of fluctuation and frequency.
Load	In 12 seconds: Records the minimum value of Voltage & Frequency. Records the maximum value of Current and the recovery time. Calculates the offset of Voltage & Frequency.
Unload	In 12 seconds: Records the maximum value of Voltage & Frequency. Record the minimum value of Current and the recovery time. Calculates the offset of Voltage & Frequency.
Wave Record	Records the real-time voltage waves by five optional modes. The recording time is between 5 seconds and 5 minutes by different modes.

LOAD BANK

KPLB-1375

KEYPOWER®
Anytime Anywhere, Power Solutions

Control Panel



MANUAL CONTROL		FUNCTION
①	Turn on / off power source	Tested power source input
②	Load imput indicator	Indicate U V W load imput normal or not
③	Control mode selection	Choose control mode: Local manual control / Touch screen control / Remote control
④	Phase sequence indicator	Indicate phase sequence of tested power right or not
⑤	Multi-function meter	Show testing parameters
⑥	Master load on / off	One step loading / unloading
⑦	Load Steps	Loading / unloading
⑧	Alarm	Load bank protection: Fan failure alarm / Overload alarm / Overvoltage alarm / Overheating alarm
⑨	Emergency stop button	Emergency stop

In addition to all manual control functions, Intelligent/remote control also contains the following functions:

- Touch screen control/remote control
- Auto loading/unloading test
- Data setting

Intelligent control system with **Mitsubishi®** PLC



Intelligent Control Interface

+86 591 83405668
+86 591 38207503
info@keypower.com

Fuzhou Gff Keypower Equipment Company Limited
Keypower Solutions (Fujian) Company Limited
Add: No. 3-1, Dongling RD, Ganzhe Street, Minhou County, Fuzhou, Fujian, China